


L1465 SERIES

MINIATURE COAXIAL CONNECTORS

Widely used in sophisticated communication electronics, these coaxial connectors are small and robust, incorporating an external circlip for maximum strength and resilience. They employ the famous 'tulip' cable clip together with a removable centre pole to enable soldering.

IMPEDEANCE:	50 ohms nominal
BREAKDOWN VOLTAGE (DC):	>2kV at sea level >500V at 30,000m
INSULATION RESISTANCE:	$\geq 10^3$ megohms
CONTACT RESISTANCE AND SCREEN CONTINUITY:	≤ 5 milliohms
TEMPERATURE RANGE (AMBIENT):	-25°C to +70°C
HUMIDITY:	A4 (BS 2011)
CABLE SIZE:	Inner 1mm Overall 4.5mm
CABLE RETENTION:	35 N depending on cable
INSERTION / WITHDRAWAL FORCE:	20 N maximum
MATERIALS:	BODY: Brass, nickel-plated
	INSULANT: RPCS, PCS and CS are methyl pentene polymer. FP and FS are polyethylene
	CENTRE POLE: FP is brass, silver plated RPCS, PCS CS and FS are beryllium copper-silver plated.

Loading Instructions – L1465 series



Dialight BLP reserve the right to change without prior notice the information contained within this leaflet

Dialight BLP Ltd., Exning Road, Newmarket, Suffolk, CB8 0AX, England
Tel: +44 (0)1638 665161 Fax: +44 (0)1638 660718 email: sales@blpcomp.com <http://www.blpcomp.com>

A subsidiary of Dialight plc